

Data Sheet

Dali

Lampada da tavolo, base e spot in alluminio anodizzato, stelo flessibile (L. 40 mm) in ottone nichelato, ottica in PMMA.

Table lamp, base and spot made of anodized aluminum, flexible stem (L. 40mm) made of nickel-plated brass, PMMA optics.

N. led 3 da 3W

Led no. 3x3W

Potenza ass. 9W

Power abs. about 9W

Alimentazione 220V tramite driver switching sulla spina o interruttore ad comando bipolare trasparente (L. 180 cm).

Feeding 220V through driver switching on the plug and switch or 180 cm transparent bipolar cable (L. 180cm).

Applicazioni scrivania, comò, tavolini, help-desk, reception.

Application On desks, chests of drawers, small tables, reception desks.



ARTICOLI / ITEM	N. LED / LED NO.	COLORI LED / LED COLOR	FASCIO / BEAM	LED (SPINA) / LED (PLUG)	FINITURA / FINISHING
DAL	3			0	A
			1 2 3	1 2 3	A

Curve fotometriche / Photometric diagrams

I diagrammi sottostanti e le relative tabelle indicano il diametro di apertura dei diversi fasci e il livello d'illuminamento di un singolo led espresso in Lux (E0= illuminamento massimo, E1= illuminamento minimo, Em= illuminamento medio). Per apparecchi dotati di più led, tali valori dovranno essere moltiplicati per il numero complessivo di led presenti nell'apparecchio. I valori di riferimento si riferiscono a 1 led NW da 1W con emissione 100 Lm; si tratta tuttavia di valori puramente indicativi e soggetti a modifiche che l'Azienda può apportare senza preavviso.

The following diagrams and the relevant tables indicate the diameters of the different beams and the level of brightness of a single led expressed in Lux (E0= maximum brightness, E1= minimum brightness, Em= medium brightness). In case of fixtures containing more than 1 led, the values must be multiplied by the total number of leds in the spot. The values refer to 1 NWx1W emitting 100Lm; anyhow they're indicative values since they can undergo some changes without any previous notice.

FASCIO 12° BEAM 12°						
ALTEZZA HEIGHT	NUM. LED LED NO.	Ø FASCIO Ø BEAM	E0 MAX	E1 6°	E MEDIO MEDIUM E	
1 mt.	1	0,21	950	670	810	
2 mt.	1	0,42	170	120	145	
3 mt.	1	0,63	75	55	65	

FASCIO 20° BEAM 20°						
ALTEZZA HEIGHT	NUM. LED LED NO.	Ø FASCIO Ø BEAM	E0 MAX	E1 10°	E MEDIO MEDIUM E	
1 mt.	1	0,35	495	345	420	
2 mt.	1	0,71	120	86	103	
3 mt.	1	1,06	30	22	26	

FASCIO 33° BEAM 33°						
ALTEZZA HEIGHT	NUM. LED LED NO.	Ø FASCIO Ø BEAM	E0 MAX	E1 16,5°	E MEDIO MEDIUM E	
1 mt.	1	0,59	320	220	270	
2 mt.	1	1,18	78	54	66	
3 mt.	1	1,77	38	26	32	