

Data Sheet

Opale

Colonnina con basetta, cilindro e calotta in alluminio anticorrosivo anodizzato, (solo cilindro disponibile anche in acciaio inox AISI 316L spazzolato) diffusore in polycarbonato satinato; fornito con cavo unipolare.

N. led 4 da 3W (+ 1 led da 0.25W nella versione con luce di cortesia)

Potenza ass. 4 W circa

Alimentazione Tramite alimentatore 12/24V DC, collegamento in parallelo rispettando le polarità. I 4 led e il led di cortesia si accendono separatamente mediante opportuno interruttore o deviatore.

Applicazioni Illuminazione di vialetti, aree residenziali.

Installazione Fissaggio basetta mediante 3 viti a filo

Note Driver elettronico a bordo

Little column with anodized aluminium base, cylinder and cap (the cylinder only is available also in satinized AISI 316L steel), satinized polycarbonate diffuser; provided with unipolar cable.

Led no. 4x3W + 1x0.25W where the courtesy light is required

Power abs. about 4 W


Feeding Through power supply 12/24V DC, parallel connection respecting polarities. The 4 leds+courtesy led light separately through a suitable switch.

Application Lighting of public or residential areas.

Installation Fixing of the base through 3 screws.

Note Electronic driver on board

CE II LED TEC F DIM IP65  h 230 Kg 2,15
h 480 Kg 2,70
h 730 Kg 3,20



ACCESSORI / ACCESSORIES

+ Alimentatore power supply 12/24V DC



ARTICOLO ITEM	N. LED LED NO.	COLORE LED LED COLOUR	FASCIO BEAM	LED CORTESIA COURTESY LED	FINITURA FINISHING	ALTEZZA HEIGHT
OPA	4		6			
	1 CW	2 NW	6 360°	0 NO	4	1 230
	3 WW	4		5	6	2 480
	5	6				3 730