

LED



## JUT IP65


Plafone a soffitto, ideale per l'illuminazione di vetrine, espositori, librerie, scaffalature, ingressi, corridoi.

Ceiling spotlight, ideal for the lighting of shop-windows, stands, bookcases, shelves, entrances, corridors.

<b>Materiale</b>	Corpo in alluminio verniciato Staffa in acciaio zincato Vetro temperato N° 4 finiture standard	
<b>N° Led</b>	1 x 4/6W	
<b>Potenza assorbita</b>	4/6W 5/7W (230V ac)	
<b>Collegamento</b>	- In serie rispettando la polarità - A rete 230V ac	
<b>Cablaggio</b>	Fornito con 25 cm di cavo	
<b>Installazione</b>	A soffitto con aggancio su staffa a scomparsa	
<b>Driver switching</b>	(non incluso alim. I) 350mA	p. 424
	(non incluso alim. I) 500mA	p. 425
<b>Fotometrie</b>		p. 417
<b>Note</b>	Versioni U e T (a binario)	p. 197
	Per configurazione RGB vedi	p. 431
	Versione IP40	p. 136

<b>Material</b>	Varnished aluminium body Zinc-coated bracket Tempered glass No. 4 standard finishings	
<b>Led no.</b>	1 x 4/6W	
<b>Power absorption</b>	4/6W 5/7W (230V ac)	
<b>Connection</b>	- series connection respecting polarities - 230V ac	
<b>Wiring</b>	Provided with a 25cm long cable	
<b>Installation</b>	On the ceiling through internal bracket	
<b>Driver switching</b>	(not included supply I) 350mA	p. 424
	(not included supply I) 500mA	p. 425
<b>Photometries</b>		p. 417
<b>Note</b>	Options T and U (track versions)	p. 197
	For RGB version see	p. 431
	IP40 version	p. 136


jut R



IP65 CE F III Supply I Supply R kg 0,600

CODE	OPTIONS	SUPPLY	N°LED	LED COLOUR	OPTICS	WATT	FINISHING
<b>JUT</b>	...	...	...	...	...	...	...
	<b>C</b> Round	<b>I</b> CC	<b>1</b>	<b>2</b> ○ 4000°K <b>3</b> ○ 3000°K <b>W</b> ○ 2700°K <b>7</b> ● RGB	<b>1</b> ▭ 16° <b>2</b> ▭ 40° <b>3</b> ▭ 64° <b>4</b> ▭ 120°	<b>4</b> <b>6</b>	<b>A</b> ▭ Anod. alu. <b>B</b> ▭ White RAL9003 <b>O</b> ▭ Black RAL9005 <b>R</b> ▭ Cor-ten
<b>JUT</b>	...	...	...	...	...	...	...
	<b>C</b> Round	<b>R</b> 230V ac	<b>1</b>	<b>2</b> ○ 4000°K <b>3</b> ○ 3000°K <b>W</b> ○ 2700°K	<b>1</b> ▭ 16° <b>2</b> ▭ 40° <b>3</b> ▭ 64° <b>4</b> ▭ 120°	<b>4</b> <b>6</b>	<b>A</b> ▭ Anod. alu. <b>B</b> ▭ White RAL9003 <b>O</b> ▭ Black RAL9005 <b>R</b> ▭ Cor-ten

jut Q



IP65 CE F III Supply I Supply R kg 0,800

CODE	OPTIONS	SUPPLY	N°LED	LED COLOUR	OPTICS	WATT	FINISHING
<b>JUT</b>	...	...	...	...	...	...	...
	<b>D</b> Square	<b>I</b> CC	<b>1</b>	<b>2</b> ○ 4000°K <b>3</b> ○ 3000°K <b>W</b> ○ 2700°K <b>7</b> ● RGB	<b>1</b> ▭ 16° <b>2</b> ▭ 40° <b>3</b> ▭ 64° <b>4</b> ▭ 120°	<b>4</b> <b>6</b>	<b>A</b> ▭ Anod. alu. <b>B</b> ▭ White RAL9003 <b>O</b> ▭ Black RAL9005 <b>R</b> ▭ Cor-ten
<b>JUT</b>	...	...	...	...	...	...	...
	<b>D</b> Square	<b>R</b> 230V ac	<b>1</b>	<b>2</b> ○ 4000°K <b>3</b> ○ 3000°K <b>W</b> ○ 2700°K	<b>1</b> ▭ 16° <b>2</b> ▭ 40° <b>3</b> ▭ 64° <b>4</b> ▭ 120°	<b>4</b> <b>6</b>	<b>A</b> ▭ Anod. alu. <b>B</b> ▭ White RAL9003 <b>O</b> ▭ Black RAL9005 <b>R</b> ▭ Cor-ten