

LED



mizar IP54


Plafone a soffitto, ideale per l'illuminazione di portici, pensiline, ingressi.

Ceiling spotlight, ideal for the lighting of porches, shelters, entrances.









Materiale	Corpo in acciaio verniciato Diffusore in PMMA N° 2 finiture standard
N° Led	2 moduli da 9W (Forma S) 2 moduli da 12W (Forma T)
Potenza assorbita	22W (230V ac) (Forma S) 29W (230V ac) (Forma T)
Collegamento	A rete 230V ac
Cablaggio	Fornito con muffole IP
Installazione	Con base mediante viti a scomparsa e vite di fissaggio
Alimentatore	(incluso) 230V ac
Fotometrie	p. 412
Note	Versione IP40 p. 150

Material	Varnished steel body PMMA diffuser No 2 standard finishings
Led no.	2 x 9W modules (Option S) 2 x 12W modules (Option T)
Power absorption	22W (230V ac) (Option S) 29W (230V ac) (Option T)
Connection	230V ac
Wiring	Provided with IP junction boxes
Installation	With support through screws and setscrew
Power supply	(included) 230V ac
Photometries	p. 412
Note	IP40 version p. 150

mizar s











IP54 CE F   kg 3,7

CODE	OPTIONS	SUPPLY	N°LED	LED COLOUR	OPTICS	WATT	FINISHING
MIZ
 S Square	R 230V ac	2	1  6000°K 2  4000°K 3  3000°K W  2700°K	4  120°	9	B  White RAL9003 O  Black RAL9005	

mizar T



IP54 CE F   kg 6,7

CODE	OPTIONS	SUPPLY	N°LED	LED COLOUR	OPTICS	WATT	FINISHING
MIZ
 T Rectangular	R 230V ac	2	1  6000°K 2  4000°K 3  3000°K W  2700°K	4  120°	12	B  White RAL9003 O  Black RAL9005	